



Tabella Tecnica

Ref Code	Part Number Mak	Size	Finished	Bolt Holes	Bolt Circle	Bolt Hole Diameter	Center Bore	Inset	Outset	Max Load
T179A	F556OYPSM612616	16X5.5	Machined/Spazzolato	6	205 mm	16	161	112	126	1320 kg
T179A	F556OYPPP612616	16X5.5	Polished Bothside/Lucido Ambo i lati	6	205 mm	16	161	112	126	1320 kg
T216A	F752OYPPP155126	19.5X7.5	Polished Bothside/Lucido Ambo i lati	10	225 mm	26	176	133	155	3000 kg
T160A	F752OYPPP15530	19.5X7.5	Polished Bothside/Lucido Ambo i lati	8	275 mm	30	221	134	155	3000 kg
T154A	F8523YPPP16732	22.5X8.25	Polished Bothside/Lucido Ambo i lati	10	335 mm	32	281	144.8	167	3650 kg
T154A	F8523YPPP16726	22.5X8.25	Polished Bothside/Lucido Ambo i lati	10	335 mm	26	281	144.8	167	3650 kg
T154A	F8523YPBII6732	22.5X8.25	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	32	281	144.8	167	3650 kg
T154A	F8523YPBII6726	22.5X8.25	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	26	281	144.8	167	3650 kg
T057A	F9023YPSM17532	22.5X9.0	Machined/Spazzolato	10	335 mm	32	281	152.1	175	4125 kg
T057A	F9023YPSM17526	22.5X9.0	Machined/Spazzolato	10	335 mm	26	281	152.1	175	4125 kg
T057A	F9023YPPP17532	22.5X9.0	Polished Bothside/Lucido Ambo i lati	10	335 mm	32	281	152.1	175	4125 kg
T057A	F9023YPPP17526	22.5X9.0	Polished Bothside/Lucido Ambo i lati	10	335 mm	26	281	152.1	175	4125 kg
T057A	F9023YPBII7532	22.5X9.0	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	32	281	152.1	175	4125 kg
T057A	F9023YPBII7526	22.5X9.0	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	26	281	152.1	175	4125 kg
T172A	F1123YPSM12032	22.5X11.75	Machined/Spazzolato	10	335 mm	32	281	120	146.3	5000 kg
T172A	F1123YPSM12026	22.5X11.75	Machined/Spazzolato	10	335 mm	26	281	120	146.3	5000 kg
T172A	F1123YPOP12032	22.5X11.75	Polished Outside/Lucido Esterno	10	335 mm	32	281	120	146.3	5000 kg
T172A	F1123YPOP12026	22.5X11.75	Polished Outside/Lucido Esterno	10	335 mm	26	281	120	146.3	5000 kg
T246B	F1123YPOP13526	22.5X11.75	Polished Outside/Lucido Esterno	10	335 mm	26	281	135	160	5000 kg
T008B	F1123YPBIO026	22.5X11.75	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	26	281	0	25	4500 kg
T172A	F1123YPBII2032	22.5X11.75	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	32	281	120	146.3	5000 kg
T172A	F1123YPBII2026	22.5X11.75	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	26	281	120	146.3	5000 kg
T246B	F1123YPBII3526	22.5X11.75	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	26	281	135	160	5000 kg
T246B	F1123YPBII3532	22.5X11.75	Full Pom-Nano/Bright/Anti Corrosione	10	335 mm	32	281	135	160	5000 kg

[illegible]